



## 5 Switches, control units, sockets and plugs



### 5 Sockets and plugs ATX

#### 9 63 A Wall sockets

The 63A sockets and plugs differ construction-wise from the versions with less power. The voltage is cut off by means of a lockable switch instead of an internal switching mechanism. The auxiliary contact can be integrated into the control circuit.

#### Specifications

Connection	35mm <sup>2</sup>
Protection	IP65
Cable entries	1 gland M50 and 1 plug M25
Material	enclosure made of impact-resistant plastic and polyamide socket
Ambiant temperature	-30°C - +55°C

II 2 G Ex db eb IIC T4 Gb

II 2 D Ex tb IIIC T80°C Db

Zone 0	✗	Zone 20	✗
Zone 1	✓	Zone 21	✓
Zone 2	✓	Zone 22	✓

INERIS20ATEX0033X



#### Ordering data

Code	No. of poles	Nom. current	Voltage	Break power (kW-AC3)	Weight
C63-230-4	3P+PE	63A	200-250 VAC	15	8 kg
C63-400-4	3P+PE	63A	380-415 VAC	22	8 kg
C63-400-5	3P+N+PE	63A	380-415 VAC	22	8 kg
C63-500-4	3P+PE	63A	480-500 VAC	18,5	8 kg

#### Dimensional sketches

